



PRODUCT DATA SHEET



Product No	8035
Issue No.	1
Issue Date	16/01/2017

PRODUCT NAME/VISCOSITIES:

MILLERMATIC ATF 8 Speed

DESCRIPTION:

Premium Automatic Transmission Fluid technology blended into selected synthetic base fluids.

APPLICATION:

Use as received in automatic transmissions and other equipment, which require this type of lubricant.

USER BENEFITS:

- Easier shifting even at low temperatures.
- Alternative to ZF Lifeguard Fluid 8 automatic transmission fluid for use in certain 8-Speed automatic transmissions
- Shorter warm up ensures max gearbox efficiency.
- Stays in grade even under extreme conditions.
- Lower maintenance costs.
- Longer drain periods.
- Excellent high temperature oxidation stability up to 100,000 miles under normal conditions
- Stable friction properties increases durability, to meet longer warranty periods.
- Outstanding low temperature fluidity which provides exceptional cold flow properties.

PERFORMANCE PROFILE:

- ZF Lifeguard 8
- BMW 83 222 152 426
- BMW 83 222 305 397 (ATF3)
- BMW 83 222 289 720 (ATF3+)
- Fiat 9.55550-AV5
- Bentley JNV 862 564 D
- VW G 060162,
- Also suitable for certain models of Chrysler, Dodge, Jaguar, Jeep, Land Rover and Maserati where an 8 speed ATF fluid is called for.





PRODUCT DATA SHEET



TYPICAL CHARACTERISTICS:

Specific Gravity @ 15°C g/ml	0.847
Kinematic Viscosity @ 100°C cSt	6.6
Kinematic Viscosity @ 40°C cSt	35.2
Viscosity Index	145
Pour Point °C	-45
Flashpoint °C	>220
Brookfield Viscosity @ -40°C cP	12,300
Colour	Green

HEALTH AND SAFETY:

Health and Safety Data Sheet 8000 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

