



PRODUCT DATA SHEET



Product No	7999
Issue No.	1
Issue Date	16/01/2017

PRODUCT NAME/VISCOSITIES:

TRX SYNTH 75W

DESCRIPTION:

A fully synthetic manual transmission oil to provide maximum protection and fuel economy.

APPLICATION:

Suitable for use where a 75W synthetic oil is required offering increased gearbox efficiency in passenger cars due to its low viscosity level that is required and specified by OEMs including BMW, Ford, Land Rover & VAG Group. Reduces fuel consumption and excellent cold temperature performance properties.

USER BENEFITS:

- The high quality of this full synthetic Low friction and reduced drag providing increased performance and improved MPG.
- Improves the quality of gear change.
- Resists the effects of high temperatures and heavy-duty use.
- The high level of mechanical protection allows extended service intervals to be used.
- Protects against wear, sludge formation, deposits and corrosion.

PERFORMANCE PROFILE:

- API GL4
- Meets the requirements of BMW MTF LT-3
- Ford WSS-M2C200-D2
- VW G 052 171
- VW G 052 178
- VW G 052 512
- VW G 052 726
- VW G 060 726
- Special transmission oil BOT 350 M3
- BMW 83 22 0 397 244
- Porsche 000 043 301 36
- Shell TF 0870

TYPICAL CHARACTERISTICS:





PRODUCT DATA SHEET



SAE Viscosity Grade	75w
Specific Gravity @ 15°C g/ml	0.840
Kinematic Viscosity @ 100°C cSt	6.1
Kinematic Viscosity @ 40°C cSt	28.9
Viscosity Index	166
Pour point °C	-57
Flashpoint °C	>170
Brookfield Viscosity @ -40°C cP	6100

HEALTH AND SAFETY:

Health and Safety Data Sheet 7999 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk