# **TECHNICAL DATA SHEET**



Product code: 8045 Sector: Automotive Issue Date: 11/08/20 Issue No: 1

# XF PREMIUM ENGINE OIL C2 FCO 0w30

Fully synthetic, mid SAPS, for use in petrol, diesel and hybrid engines.

# **Application**

A premium manufacturer acknowledged engine oil formulated using the latest technology for OEM applications requiring a C2 0w30 viscosity, predominantly for Ford and Jaquar Land Rover.

#### Performance Profile

ACEA C2

Ford WSS-M2C950-A (Acknowledged) Jaguar Land Rover STJLR.03.5007 (Acknowledged)

#### Suitable for

**API SN** Asian manufacturers

### **Typical Characteristics**

Density @ 15°C, g/ml	0.845
Kinematic Viscosity @ 100°C, cSt.	9.7
Flashpoint. °C	>200

## Features & Benefits

- XF Premium engine oil with Millers Oils Dynamic Fluid Technology (DFT) provides enhanced low temperature flow when cold starting, instantly protecting the vital components of the engine from the very start of every journey.
- XF Premium engine oil with DFT maximises viscosity stability at high temperatures. This reduces engine wear giving superior protection for components including pistons, rings, timing chain, bearings and valve lifters.
- DFT specifically engineered to enhance engine cleanliness, delivering improved fuel economy, reduced emissions and extended service drain capability.
- DFT complements and utilises latest mid SAPS technology protecting after treatment systems such as particulate filters, Selective Catalytic Reduction (SCR) and AdBlue delivering our ultimate soot control and environmental protection.
- DFT delivers outstanding instant protection under hot and cold temperatures, whilst simultaneously reducing fuel consumption and lowering exhaust emissions.
- XF Premium engine oil with DFT is specifically formulated for use in all hybrid systems including self-charging hybrid electric vehicles (HEV) and plug in hybrid electric vehicles (PHFV).

# Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk

Footnotes: SAPS – Sulphated Ash, Phosphorus & Sulphur, DFT – Dynamic Fluid Technology, OEM - Original Equipment Manufacturer





