

# TECHNICAL DATA SHEET



**Product code:** 8325 **Sector:** Automotive (Passenger car & LCV) **Issue No:** 1 **Issue Date:** 03/04/23

## EE Performance MTF 75w90

Fully synthetic gear oil with ester technology for use in gearboxes, transfer cases & differentials.

### Application

A performance gear oil featuring NANODRIVE low friction technology to provide maximum protection and performance. Predominantly for European and Asian manufacturers.

### Suitable for

API GL-4, GL-5

BMW Group Inc. Mini, Rolls Royce MTF LT-4, OSP  
Fiat Chrysler Automobiles Inc. Abarth, Alfa Romeo,  
Dodge, Ferrari, Jeep, Lancia, Maserati (pre-2021)  
9.55550-MZ11, 9.55550-DA7

Ford M2C203-A1, M2C201-A, M2C200-C (BOT  
130),

M2C200-B, M2C197-A, M2C175-A, N052145 VX00

General Motors Inc. Buick, Cadillac, Chevrolet,  
GMC, Opel, Saturn, Vauxhall (pre-2017),

GM 89021806/89021807, GM 89021677/89021678,

GM 88900401/89021678, GM 1940757,

GM 19351882/19351883, GM 9986285

Jaguar XH-21

Mercedes-Benz MB 235.8, 235.72, 235.0

Volvo 97309

VW Group Inc. Audi, Seat, Skoda,

Bentley, Lamborghini,

G51, G50, P/N G 005 000,

TL 529 11 P/N G 052 911,

TL 521 45 P/N G 052 145,

TL 501 50 P/N G 050 150,

Porsche P/N 999.917.546.00,

P/N 999.917.067.00, P/N 000.043.210.12,

P/N 000.043.207.76, P/N 000.043.204.20,

P/N 000.043.204.19

BOT 328, BOT 130

### Features & Benefits

- Reduced driveline losses from award winning NANODRIVE low friction technology, synthetic base oil with Ester formulation.
- Extended component life and reduced operating temperatures as a result of the instant lubrication provided by NANODRIVE low friction technology.
- "Track day ready", high performance oil; delivers maximum performance whilst meeting manufacturer's specifications and recommended oil drain interval for on-road use.
- Maximised efficiency and performance delivered from the low friction NANODRIVE formulation.
- Synthetic base oil and Ester combined with NANODRIVE technology gives ultimate component protection.
- EE Performance gear oil is specifically formulated for use in hybrid systems including self-charging hybrid electric vehicles (HEV) and plug in hybrid electric vehicles (PHEV).
- Covers a wide range of manufacturers including the latest gearbox, transfer case & differential technology.

### Typical Characteristics

Density @ 15°C, g/ml	0.876
Kinematic Viscosity @ 100°C, cSt	14.8
Flash Point, °C	>200

### Technical & Health and Safety

T: 01484 475060

E: [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

For H&S info or SDS, please visit our website

[www.millersoils.co.uk](http://www.millersoils.co.uk)

**Footnotes:** P/N – OEM Part Number



**MADE IN BRITAIN**

Millers Oils Ltd  
Brighouse West Yorkshire HD6 3DP UK  
Tel: +44(0) 1484 713201  
[www.millersoils.co.uk](http://www.millersoils.co.uk)