TECHNICAL DATA SHEET



Product code: 8374 Sector: Automotive Issue No: 2 Issue Date: 01/09/22

XF Premium MTF 75w

Fully synthetic gear oil for use in gearboxes.

Application

A premium OEM gear oil formulated using the latest technology for gearbox applications requiring 75w. Predominantly for European and Asian manufacturers.

Suitable for

API GL-4

BMW Group (Inc. Mini, Rolls Royce) MTF LT-3, (P/N 83 22 0 397 244) Ford M2C200-E1, M2C200-D3, M2C200-D2 General Motors (Inc. Buick, Cadillac, Chevrolet, GMC, Opel, Saturn, Vauxhall (pre-2017)), GM 19259105 (BOT 303), 19259104, 1940004 Nissan (P/N 999MP-TF0870P) PSA (Inc. Peugeot, Citroen, DS), 9730 A8, (P/N 1618078480) VW Group (Inc. Audi, Seat, Skoda) TL 726 (P/N G 070 726), TL 726 (P/N G 060 726), TL 726 (P/N G 055 726), TL 726 (P/N G 052 726), TL 525 27 (P/N G 052 527), (P/N G 055 512), TL 525 12 (P/N G 052 512), TL 521 78 (P/N G 052 178), TL 521 71 (P/N G 052 Porsche (P/N 000.043.301.36)

BOT 350 M3 TF 0870

Features & Benefits

- XF Premium gear oil provides enhanced low temperature flow when cold starting, instantly protecting the vital components of the gearbox from the very start of every journey.
- XF Premium gearbox oil maximises viscosity stability at high temperatures. This reduces gearbox wear giving superior component protection including gear teeth, shafts and bearings.
- Delivers outstanding lubrication and instant protection under hot and cold temperatures, whilst simultaneously reducing fuel consumption due to its low viscosity.
- XF Premium gear oil is specifically formulated for use in hybrid systems including selfcharging hybrid electric vehicles (HEV) and plug in hybrid electric vehicles (PHEV).

Typical Characteristics

Density @ 15°C, g/ml 0.847 Kinematic Viscosity @ 100°C, cSt 6.1 Flash Point, °C >200

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk

Footnotes: P/N – OEM Part Number





