

TECHNICAL DATA SHEET



Product code: 8596 **Sector:** Automotive (Passenger Car & LCV) **Issue No:** 1 **Issue Date:** 20/05/24

EE PERFORMANCE ENGINE OIL C5 V 0w20

Fully synthetic, mid SAPS, for use in petrol/gasoline & diesel engines including hybrid applications.

Application

A performance engine oil featuring NANODRIVE low friction technology for vehicles requiring a 0w20 viscosity, Designed for Volkswagen Audi Group (VAG) including Bentley, Cupra, Seat, Skoda and Porsche.

Other coverage includes European and Asian manufacturers.

Recommended for

ACEA C5

Porsche C20

VW 508 00 / 509 00

Volkswagen Audi Group including Bentley, Cupra, Seat and Skoda

Asian manufacturers

Typical Characteristics

Density @ 15°C, g/ml	0.848
Kinematic Viscosity @ 100°C, cSt.	8.12
Flashpoint, °C	>200

Features & Benefits

- Increased engine power and torque from award winning NANODRIVE low friction technology and synthetic ester formulation.
- Extended component life and reduced operating temperatures as a result of the instant lubrication provided by NANODRIVE low friction technology.
- “Track day ready”, high performance oil; delivers maximum engine performance whilst meeting manufacturer’s specifications and recommended oil drain interval for on-road use.
- Maximised efficiency and MPG delivered from the combined low viscosity and low friction NANODRIVE formulation.
- Covers a wide range of Asian/Japanese manufacturers including the latest petrol/gasoline & diesel engine technology including hybrid applications.

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk